



# DyNet-SFLAT6-CABLE

Flat Cable

Cable roll and cable kits for faster installation

Flat data cable is specifically designed for high reliability localized network wiring. In addition to a conductor pair for data, conductors are provided to supply DC power to network powered devices.

# DyNet-SFLAT6-CABLE

## Cable roll and cable kits for faster installation

- **Overall shield for maximum data integrity** – The data cable is flexible and all conductors are stranded.
- **Fast termination** – Designed for rapid crimp termination into RJ12 plugs for use with Philips Dynalite products supporting RJ12 sockets.
- **Supply options** – Available in 200 m rolls or in pre-terminated leads of 3, 5 and 10 m lengths.
- **Utilize DDPB22-RJ12 network junction box for faster installation** – Facilitates termination of 22 DyNet flat cables in one location.

## Specifications

Due to continuous improvements and innovations, specifications may change without notice.

### Electrical

Conductor DC Loop Resistance	240 Ω/km (max)
Drain DC Resistance	40 Ω/km (max)

### Conductors

Wires	5 x 0.14 mm <sup>2</sup> (#26 AWG) 12-strand
Insulation	Polyethylene HDPE Ø 1 mm ± 0.02 mm
Colors	White Red Green Yellow Black Silver (shield)
Shielding	Aluminum/polyester tape
Drain Wire	Foil-wrapped copper 0.2 mm <sup>2</sup> (#24 AWG) 9-strand

### Physical

Dimensions (Cross-Section)	2.65 x 6.95 mm (0.104 x 0.274 in)
Packed Weight	8 kg / 200 m roll (17.6 lb / 656 ft roll)
Outer Jacket Construction	PVC
Outer Jacket Color	Orange

### Environment

Installation Temperature	0° to 50°C ambient (32° to 122°F)
Operating Temperature	-20° to 50°C ambient (-4° to 122°F)
Storage/Transport Temperature	-25° to 60°C ambient (-13° to 140°F)
Humidity	0 to 90% non-condensing

## Ordering Code

Product	Philips 12NC
DYNET-SFLAT6-CABLE (200 m roll)	913703095009
DYNET-SFLAT6-CABLE-10M (10 m lead, RJ12 termination)	913703041109
DYNET-SFLAT6-CABLE-5M (5 m lead, RJ12 termination)	913703041209
DYNET-SFLAT6-CABLE-3M (3 m lead, RJ12 termination)	913703041309



© 2020 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.